



SPECIFICATIONS

Nominal Diameter	260 mm (in)
Nominal Impedance	8 Ω
Minimum Impedance	6.4 Ω
Nominal Power Handling ¹	400 W
Continuous Power Handling ²	500 W
Sensitivity ³	102.0 dB
Frequency Range	80 - 5200 Hz
Voice Coil Diameter	75 mm (3.0 in)
Winding Material	aluminum

DESIGN

Surround Shape	M-roll
Cone Shape	Curvilinear
Magnet Material	Ferrite
Woofer Cone Treatment	Weather protected
Recommended Enclosure	20.0 dm ³ (0.71 ft ³)

PARAMETERS⁴

Resonance Frequency	70 Hz
Re	5.2 Ω
Qes	0.25
Qms	4.5
Qts	0.23
Vas	25.6 dm ³ (0.9 ft ³)
Sd	350.0 cm ² (54.25 in ²)
Xmax	4.0 mm
Mms	32.0 g
Bl	17.6 Txm
Le	1.28 mH
EBP	280 Hz

MOUNTING AND SHIPPING INFO

Overall Diameter	260 mm (10.24 in)
Bolt Circle Diameter	244 mm (9.61 in)
Baffle Cutout Diameter	232.0 mm (9.13 in)
Depth	126 mm (4.96 in)
Flange and Gasket Thickness	14 mm (0.55 in)
Net Weight	7.35 kg (16.2 lb)
Shipping Weight	7.8 kg (17.2 lb)
Shipping Box	275 x 275 x 164 mm (10.83x10.83x6.46 in)

1. 2 hours test made with continuous pink noise signal within the range Fs-10Fs. Power calculated on rated nominal impedance. Loudspeaker in free air.
2. Power on Continuous Program is defined as 3 dB greater than the Nominal rating.
3. Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.
4. Thiele-Small parameters are measured after a high level 20 Hz sine wave preconditioning test.